

DÉCOR

DECORATIVE PRODUCTS FOR
INTERNAL AND EXTERNAL WALLS

CATALOG



**THE POWER
IS IN OUR
HANDS**

DÉCOR

DECORATIVE PRODUCTS FOR
INTERNAL AND EXTERNAL WALLS

BK-Deco Acryl Primer for decorative materials

Use: Acrylic primer designed to provide uniformity, neutralization and enhance the adhesion of interior decorative paints. Due to its fine particles, it creates a slightly relief surface on which the materials can be easily applied. It is not used as a primer for BK-Stucco. BK-Deco Acryl primer can be tinted with BK-Color tinting agents, if necessary.

Preparation and application: The surface to which the primer is applied must be solid, clean and dry, free from grease and oil residues. The suitable substrates to which BK-Deco Acryl is applied are all surfaces leveled with BK-GletEx Universal or BK-GletEx Acryl. BK-Deco Acryl primer should be mixed and diluted with 10% of water before use. The primer is applied with a brush in a single layer (applied by cross motions to create additional structure). The primer drying time is min. 6 h. see the product data sheet for detailed instructions.

Shelf life and storage: Up to 18 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Consumption: Approximately 0.13-0.15 l/m² depending on absorption and roughness of the surface.

Package: 1 l



BK-Sunset

Decorative paint with pearlescent effect for interior walls



Use: Special, water-washable, acrylic paint intended for interior decoration. All substrates leveled with BK-GletEx Universal or BK-GletEx Acryl are suitable.

Shades: Silver, Gold and S10. BK-Sunset Silver and BK-Sunset Gold are used as the base for tinting according to the appropriate color chart.

Preparation and application: The surface to which compound is applied must be solid, clean and dry, with no loose parts, free of oil stains and similar. Before applying the decorative paint, the leveled surfaces should be coated with BK-Deco Acryl primer (drying time min. 6 h). BK-Sunset paint is ready-to-apply. It is applied with a paint brush in one or two coats, depending on the desired effect, which is often the final step, because the use of brush on the wall creates interesting patterns. If desired, the surface finish can also be performed with a plastic hand fan. Paint is applied without interruption on continuous surfaces. BK-Sunset can also be applied to surfaces painted with BK-Gold or BK-Crystal. Optimum application temperature: from +8°C to +30°C. The coat is completely dry after 24 h. See product datasheet for more detailed instructions.

Consumption: Approximately 0,10-0,13 l/m² depending on the application technique.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 1 l; 3 l

BK-Iskra

Decorative crystal effect paint for interior walls



Use: Special acrylic paint intended for interior decoration. The brilliant final structure comes from shiny crystals that give the full color effect. Suitable substrates are all surfaces leveled with BK-GletEx Acryl or BK-GletEx Universal. Coated surfaces are resistant to wet wiping.

Shades: White+shades in accordance with BK-Iskra color chart.

Preparation and application: Before applying the decorative paint, the leveled surfaces should be coated with BK-Deco Acryl (drying time min. 6 h). For a more pronounced color effect, BK-Deco Acryl primer should be tinted in a shade of finishing coat. Paint preparation is performed by adding one pack of BK-Kristali to 1 liter of paint. Stir the compound gently and apply undiluted paint with a paint brush in to coats. The first coat of paint is applied without interruption on continuous surfaces from one side of the wall to the other, making it necessary to make a slight diagonal to avoid visible material joints and drying of the material. The second layer is applied after drying the first one (about 6 h) by the same procedure starting from the opposite side of the wall surface. Optimum application temperature: from 8°C to 35°C. The coat is completely dry after 24 h. See product datasheet for more detailed instructions.

Consumption: Approximately 0,15-0,20 l/m², depending on the application technique.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 1 l

BK-Perla

Decorative compound in the form of paste with pearly shine for indoor use

Use: Acrylic compound in the form of paste intended for interior decoration, of excellent vapor permeability and resistance to microorganisms. Due to special additives, the coating is characterized by a fine, mother-of-pearl structure. Suitable substrates are all surfaces leveled with BK-GletEx Acryl or BK-GletEx Universal. The coating is resistant to wet wiping.

Shades: silver, gold, mother of pearl+shades according to BK-Perla color chart.

Preparation and application: Before applying the decorative paint, the leveled surfaces should be coated with BK-Deco Acryl primer (drying time min. 6 h). BK-Perla is a ready-to-apply material. Stir the mixture gently. The first coat is applied with a hard plastic putty knife with one side rounded. The second and third coats are applied after complete drying of the first whereby the desired textural effects are achieved by using a plastic rounded putty knife by various application techniques. Drying time between application of coats is 6-8 h. Optimum application temperature: from 8°C to 35°C. The coat is completely dry after 24 h. See product datasheet for more detailed instructions.

Consumption: Approximately 0,20-0,30 l/m², depending on the application technique.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 1 l



BK-Velatura

Transparent coating for decorative techniques

Use: BK-Velatura is a semi-transparent acrylic paint with silicone additives intended for special effects in various decorative techniques. Recommended for indoor and outdoor use. The coating is resistant to wet wiping.

Shades: according to BK-Velatura color chart

Preparation and application: The surface to which compound is applied must be solid, clean and dry. BK-Velatura is a ready-to-apply material. Stir the mixture gently. In case of application on highly absorbent surfaces (eg BK Travertino), it is necessary to pre-impregnate the surface with BK-Penetrante in order to reduce and equalize the absorbency. The material is applied with a long-haired brush, roller or sponge gradually on smaller areas of 1-2 m². The final look is achieved by wiping with a sponge while the material is still wet. Optimal operating temperature from +5°C to +30°C. The coating is completely dry after 24 hours. See product datasheet for more detailed instructions.

Consumption: Approximately 0,05-0,10 l/m², depending on the application technique.

Shelf life and storage: 18 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 1 l



BK-Natura

Decorative compound in the form of paste with the appearance of natural materials for interior walls

Use: Compound in the form of paste intended for interior decoration. The final structure is obtained by different application techniques and the use of different tools (imitation of wood, crocodile leather, marble, etc.). The dry coating is decorated with transparent BK-Velatura paint. Suitable substrates are all surfaces leveled with BK-GletEx Acryl or BK-GletEx Universal. The coating is resistant to wet wiping.

Shades: White+shades in accordance with BK-Natura color chart.

Preparation and application: Before applying the decorative paint, the leveled surfaces should be coated with BK-Deco Acryl primer (drying time min. 6 h). BK-Natura is a ready-to-apply material. Stir the compound lightly and apply with trapezoidal plastic putty knife in one layer. After application, the fresh material is treated with a rounded plastic putty knife, a 'comb' for decorative materials, rollers with textures and similar tools, depending on the desired structure. After drying for 24 h, an additional effect is achieved by applying BK-Velatura paint. Optimum application temperature: from 8°C to 35°C. The coat is completely dry after 24 h. See product datasheet for more detailed instructions.

Consumption: approx 0,30-0,50 l/m², depending on the application technique.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 5 l



BK-NovaEra Exclusive Decorative paint with antique effect for interior walls

Use: Acrylic vapor permeable paint for interior decoration. All surfaces leveled with BK-GletEx Universal or BK-GletEx Acryl are appropriate. Painted surfaces are resistant to wet wiping.

Shades: Gold, silver or bronze.

Preparation and application: Before applying the decorative paint, the leveled surfaces should be coated with BK-Deco Acryl primer (drying time min. 6 h). After applying the primer, BK-Gold or BK-Crystal should be applied in the desired shade, and after drying the paint BK-NovaEra Exclusive can be applied. The paint is applied with a paint brush, usually in one coat. The final appearance is achieved by flattening with a plastic hand fan. Optimum application temperature: from +8°C to +35°C. The time required for drying until applying the subsequent coat is 4 -6 h. The coat is completely dry after 24 h. See product datasheet for more detailed instructions.

Consumption: About 0,20-0,30 l/m² for a single coat.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 1 l



BK-NovaEra Decorative paint with antique effect for interior walls

Use: Acrylic vapor permeable paint for interior decoration. All surfaces leveled with BK-GletEx Universal or BK-GletEx Acryl are appropriate. Painted surfaces are resistant to wet wiping.

Shades: White+shades in accordance with BK-Nova Era color chart.

Preparation and application: Before applying the decorative paint, the leveled surfaces should be coated with BK-Deco Acryl primer (drying time min. 6 h). It is usually applied with a paint brush, in two layers. The final appearance is achieved by flattening with a plastic hand fan. Optimum application temperature: from +8°C to +35°C. The time required for drying until applying the subsequent coat is min. 4-6 h. The coat is completely dry after 24 h. Mixing is done exclusively by hand. See product datasheet for more detailed instructions.

Consumption: About 0,20-0,30 l/m² for a single coat.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 2,5 l



BK-Travertino Exterior&Interior

Decorative mineral render with rustic effect for interior and exterior walls



Use: BK-Travertino Exterior&Interior is a precious mineral render intended for decorative protection of interior and exterior surfaces. It is characterized by excellent adhesion to mineral surfaces, exceptional water repellency, as well as, resistance to atmospheric influences and UV radiation. It provides high vapor permeability and excellent resistance to the development of microorganisms. BK-Travertino is produced exclusively in white color and subsequently is coated with a transparent BK-Velatura coating, after drying for at least 24 hours under normal conditions.

Preparation and application: The surface to which the render is applied must be flat, dry, clean, free from loosely bonded parts, dust, water-soluble salts, grease and other impurities, which can prevent good adhesion to the substrate. Suitable substrates are cement-lime mortars, reinforcement layer of thermal insulation systems, gypsum cardboards and cement-fiber boards. Before applying the decorative render coat the substrate with BK-Ultra Prime primer and in the case of smooth surfaces perform priming using the BK-Grund Universal. The preparation of the compound is done by adding the powder to about 25% of water to achieve a homogeneous mixture, without lumps (8 kg of powder requires ~ 2l of water; 20 kg of powder requires ~ 5l of water). Allow the compound to rest for at least 10-15 minutes, before stirring once more, and if necessary add water to adjust the consistency. Use prepared compound within 2 hours. BK-Travertino is applied in two coats with a stainless trowel. Apply the first coat evenly in an approximate thickness of 1-2 mm. The second coat is applied after complete drying of the first one (about 6 hours at normal drying). The creation of the texture of natural stone is achieved with the appropriate tool by which irregular recesses, characteristic of travertine stone, are created. The added effect of the render is achieved by lightly leveling with a metal trowel when the material begins to "pull". When the material is surface-dried (about 2 hours when drying under normal conditions) it is possible to form the appearance of joints with the proper tool to imitate the look of stone blocks. See product datasheet for more detailed instructions.

Application temperature: The air and substrate temperatures during installation should be in the range from +5 °C to +30 °C. Do not work under direct sunlight, fog, wind or rain.

Consumption: Approximately 2,5-2,7 kg/m², depending on technique and thickness of application.

Shelf life and storage: 18 months in original sealed packing. Store at +5°C to +25°C, in a dry and well-ventilated room.

Package: 20 kg

BK-Stucco

Decorative mass for interior walls



Use: High quality decorative mass designed for interior decoration. All surfaces leveled with BK-GletEx Universal or BK-GletEx Acryl are appropriate.

Shades: White+shades according to BK-Stucco color chart. The shades can be mixed in an arbitrary ratio.

Preparation and application: Before applying the decorative technique, the leveled surfaces must be coated with BK-Podloga (drying time min. 6 h). If required BK-Stucco can be diluted with water max. up to 3%. It is applied with stainless steel trowel in minimum of three layers. The structure is obtained by processing with a metal trowel while the material is in a paste form, by various techniques depending on the desired effect. The final look is obtained by polishing the dry material with a metal trowel. In case of need for high gloss effect additional polishing with protective wax is necessary. The BK-Stucco is resistant to wet wiping if waxed. Optimum application temperature: from +8°C to +35°C. Time of drying until the application of the next coat is 4-6 h depending on the thickness of the coat. See product datasheet for more detailed instructions.

Consumption: Approximately 0,30-0,50 kg/m² depending on the application technique.

Shelf life and storage: 12 months in original sealed packing. Store at temperatures from +5°C to +25°C, protected from direct sunlight and frost.

Package: 3,5 kg



Banja Komerc Bekament DOO
Arandjelovac, 34304 Banja, Serbia
Tel: +381 34 6777 500; Fax: +381 34 6777 506
www.bekament.com