



### **BK-Silicon Neutral Profi**

# SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

**1.1 Product identifier:** BK-Silicon Neutral Profi

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Sealant

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Banja Komerc Bekament d.o.o. Kralja Petra Prvog 132 34304 Banja, Arandjelovac, Serbia Phone.: +38162255631 dragana.kuc@bekament.com http://bekament.com

1.4 Emergency telephone number: 911

# SECTION 2: HAZARDS IDENTIFICATION \*\*

### 2.1 Classification of the substance or mixture:

### CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

## 2.2 Label elements:

## CLP Regulation (EC) No 1272/2008:

## **Hazard statements:**

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

# **Precautionary statements:**

P273: Avoid release to the environment.

P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment.

# **Supplementary information:**

EUH208: Contains octhilinone (ISO). May produce an allergic reaction.

### 2.3 Other hazards:

Product contains PBT/vPvB substances: Octamethylcyclotetrasiloxane

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

# 3.1 Substance:

Non-applicable

## 3.2 Mixture:

**Chemical description:** Aqueous mixture based on silicones

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

	Identification		Chemical name/Classification		Concentration
CAS:	37859-55-5	O,O',O''-(methylsily	lidyne)trioxime 2-pentanone <sup>(1)</sup>	Self-classified	
	484-460-1 Non-applicable Non-applicable	Regulation 1272/2008	Acute Tox. 4: H302; Eye Irrit. 2: H319 - Warning	<u>(1)</u>	1 - <5 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

<sup>\*\*</sup> Changes with regards to the previous version



### This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

### **BK-Silicon Neutral Profi**

# SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification	Chemical name/Classification		Concentration
CAS: EC: Index: REACH:	919-30-2 213-048-4 612-108-00-0 01-2119480479-24- XXXX	3-aminopropyltriethoxysilane(1) Regulation 1272/2008 Acute Tox. 4: H302; Skin Corr. 1B: H314 - Danger	ATP CLP00	0.1 - <1 %
CAS: EC: Index: REACH:	556-67-2 209-136-7 014-018-00-1 01-2119529238-36- XXXX	Octamethylcyclotetrasiloxane(1)  Regulation 1272/2008 Aquatic Chronic 1: H410; Flam. Liq. 3: H226; Repr. 2: H361f - Warning	ATP ATP15	0.01 - <0.1
CAS: EC: Index: REACH:	26530-20-1 247-761-7 613-112-00-5 01-2120768921-45- XXXX	Octhilinone (ISO)(1)   Regulation 1272/2008   Acute Tox. 2: H330; Acute Tox. 3: H301+H311; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1: H314; Skin Sens. 1A: H317; EUH071 - Danger	ATP ATP15	0.0015 - <0.01 %

<sup>(1)</sup> Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

## **SECTION 4: FIRST AID MEASURES**

### 4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

### By inhalation:

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

# By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

### By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as guickly as possible with the SDS for the product.

## By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

# 4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

## 4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

# **SECTION 5: FIREFIGHTING MEASURES**

# 5.1 Extinguishing media:

## Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

# Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

## 5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

## 5.3 Advice for firefighters:

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

### **BK-Silicon Neutral Profi**

# SECTION 5: FIREFIGHTING MEASURES (continued)

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

# **Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

## 6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

## 6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

#### 6.4 Reference to other sections:

See sections 8 and 13.

## SECTION 7: HANDLING AND STORAGE

# 7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

## 7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C


Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

## 7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.





## **BK-Silicon Neutral Profi**

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no occupational exposure limits for the substances contained in the product

## **DNEL (Workers):**

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
O,O´,O´´-(methylsilylidyne)trioxime 2-pentanone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 37859-55-5	Dermal	Non-applicable	Non-applicable	0,065 mg/kg	Non-applicable
EC: 484-460-1	Inhalation	Non-applicable	Non-applicable	0,229 mg/m <sup>3</sup>	Non-applicable
3-aminopropyltriethoxysilane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 919-30-2	Dermal	Non-applicable	Non-applicable	2 mg/kg	Non-applicable
EC: 213-048-4	Inhalation	Non-applicable	Non-applicable	14 mg/m³	Non-applicable
Octamethylcyclotetrasiloxane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 556-67-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable
EC: 209-136-7	Inhalation	Non-applicable	Non-applicable	73 mg/m <sup>3</sup>	73 mg/m³

# **DNEL (General population):**

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
O,O´,O´´-(methylsilylidyne)trioxime 2-pentanone	Oral	Non-applicable	Non-applicable	0,033 mg/kg	Non-applicable	
CAS: 37859-55-5	Dermal	Non-applicable	Non-applicable	0,033 mg/kg	Non-applicable	
EC: 484-460-1	Inhalation	Non-applicable	Non-applicable	0,057 mg/m <sup>3</sup>	Non-applicable	
3-aminopropyltriethoxysilane	Oral	Non-applicable	Non-applicable	1 mg/kg	Non-applicable	
CAS: 919-30-2	Dermal	Non-applicable	Non-applicable	1 mg/kg	Non-applicable	
EC: 213-048-4	Inhalation	Non-applicable	Non-applicable	3,5 mg/m <sup>3</sup>	Non-applicable	
Octamethylcyclotetrasiloxane	Oral	Non-applicable	Non-applicable	3,7 mg/kg	Non-applicable	
CAS: 556-67-2	Dermal	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
EC: 209-136-7	Inhalation	Non-applicable	Non-applicable	13 mg/m <sup>3</sup>	13 mg/m <sup>3</sup>	


# PNEC:

Identification				
O,O´,O´´-(methylsilylidyne)trioxime 2-pentanone	STP	2,15 mg/L	Fresh water	0,1 mg/L
CAS: 37859-55-5	Soil	0,044 mg/kg	Marine water	0,01 mg/L
EC: 484-460-1	Intermittent	Non-applicable	Sediment (Fresh water)	0,569 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,057 mg/kg
3-aminopropyltriethoxysilane	STP	1,3 mg/L	Fresh water	Non-applicable
CAS: 919-30-2	Soil	Non-applicable	Marine water	Non-applicable
EC: 213-048-4	Intermittent	Non-applicable	Sediment (Fresh water)	Non-applicable
	Oral	Non-applicable	Sediment (Marine water)	Non-applicable
Octamethylcyclotetrasiloxane	STP	10 mg/L	Fresh water	0,0015 mg/L
CAS: 556-67-2	Soil	0,54 mg/kg	Marine water	0,00015 mg/L
EC: 209-136-7	Intermittent	Non-applicable	Sediment (Fresh water)	3 mg/kg
	Oral	0,041 g/kg	Sediment (Marine water)	0,3 mg/kg
octhilinone (ISO)	STP	Non-applicable	Fresh water	0,0022 mg/L
CAS: 26530-20-1	Soil	0,0082 mg/kg	Marine water	0,00022 mg/L
EC: 247-761-7	Intermittent	0,00122 mg/L	Sediment (Fresh water)	0,0475 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00475 mg/kg

# 8.2 Exposure controls:

A.- General security and hygiene measures in the work place

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.





## **BK-Silicon Neutral Profi**

# SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Protective gloves against minor risks	CATI		Replace gloves in case of any sign of damage. For prolonged periods of exposure to the product for professional users/industrials, we recommend using CE III gloves in line with standards EN 420:2004+A1:2010 and EN ISO 374-1:2016+A1:2018

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

## D.- Ocular and facial protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

## E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CATII	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

# F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

# **Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

## Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 0,1 % weight

V.O.C. density at 20 °C: 1,09 kg/m³ (1,09 g/L)

Average carbon number: 8

Average molecular weight: 296,6 g/mol

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

# 9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

# Appearance:

Physical state at 20 °C: Liquid

\*Not relevant due to the nature of the product, not providing information property of its hazards.

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation



### **BK-Silicon Neutral Profi**

# SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Appearance: Paste

Colour: According to the markings on the package

Odour: Characteristic
Odour threshold: Non-applicable \*

Volatility:

Boiling point at atmospheric pressure:

Vapour pressure at 20 °C:

Vapour pressure at 50 °C:

Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

**Product description:** 

Density at 20 °C: Non-applicable \*

Relative density at 20 °C: 1,02

Dynamic viscosity at 20 °C: Non-applicable \*

Kinematic viscosity at 20 °C: >21 cSt
Kinematic viscosity at 40 °C: >20,5 cSt

Concentration: Non-applicable \*

Partition coefficient n-octanol/water 20 °C: Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

Solubility in water at 20 °C:

Solubility properties:

Decomposition temperature:

Melting point/freezing point:

Explosive properties:

Oxidising properties:

Non-applicable \*

Non-applicable \*

Non-applicable \*

Non-applicable \*

Flammability:

Flash Point: >100 °C

Heat of combustion:

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Non-applicable \*

Non-applicable \*

Non-applicable \*

**Explosive:** 

Lower explosive limit:

Upper explosive limit:

Non-applicable \*

Non-applicable \*

9.2 Other information:

Surface tension at 20 °C: Non-applicable \*

Refraction index: Non-applicable \*

\*Not relevant due to the nature of the product, not providing information property of its hazards.

# SECTION 10: STABILITY AND REACTIVITY

## 10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

## 10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

Date of compilation: 04/11/2017 Revised: 04/11/2021 Version: 3 (Replaced 2) **Page 6/11** 



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

### **BK-Silicon Neutral Profi**

# SECTION 10: STABILITY AND REACTIVITY (continued)

# 10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

#### 10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

### 10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

#### 10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO2), carbon monoxide and other organic compounds.

# SECTION 11: TOXICOLOGICAL INFORMATION

## 11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

## **Dangerous health implications:**


In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
  - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
  - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for inhalation. For more information see section 3.
  - Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
  - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous for skin contact. For more information see section 3.
  - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
  - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.

IARC: Non-applicable

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met. However, it does contain substances classified as dangerous for this effect. For more information see section 3.
- E- Sensitizing effects:
  - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
  - Cutaneous: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.





## **BK-Silicon Neutral Profi**

# SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- G- Specific target organ toxicity (STOT)-repeated exposure:
  - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
  - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

### Other information:

Non-applicable

# Specific toxicology information on the substances:

Identification Acute toxicity		cute toxicity	Genus	
3-aminopropyltriethoxysilane	LD50 oral	1491 mg/kg	Rat	
CAS: 919-30-2	LD50 dermal	4000 mg/kg	Rabbit	
EC: 213-048-4	LC50 inhalation	Non-applicable		
O,O´,O´´-(methylsilylidyne)trioxime 2-pentanone	LD50 oral	1234 mg/kg	Rat	
CAS: 37859-55-5	LD50 dermal	Non-applicable		
EC: 484-460-1	LC50 inhalation	Non-applicable		
octhilinone (ISO)	LD50 oral	125 mg/kg		
CAS: 26530-20-1	LD50 dermal	311 mg/kg		
EC: 247-761-7	LC50 inhalation	Non-applicable		

# **SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

# 12.1 Toxicity:

Identification		Acute toxicity	Species	Genus
3-aminopropyltriethoxysilane	LC50	Non-applicable		
CAS: 919-30-2	EC50	331 mg/L (48 h)	Daphnia magna	Crustacean
EC: 213-048-4	EC50	603 mg/L (72 h)	Scenedesmus subspicatus	Algae
Octamethylcyclotetrasiloxane	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 556-67-2	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 209-136-7	EC50	>0.1 - 1 mg/L (72 h)		Algae
octhilinone (ISO)	LC50	>0.1 - 1 mg/L (96 h)		Fish
CAS: 26530-20-1	EC50	>0.1 - 1 mg/L (48 h)		Crustacean
EC: 247-761-7	EC50	>0.1 - 1 mg/L (72 h)		Algae

# 12.2 Persistence and degradability:

Identification	Degradability		Biodegradability	
3-aminopropyltriethoxysilane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 919-30-2	COD	Non-applicable	Period	28 days
EC: 213-048-4	BOD5/COD	Non-applicable	% Biodegradable	54 %

## 12.3 Bioaccumulative potential:

Identification	Bio	Bioaccumulation potential		
3-aminopropyltriethoxysilane	BCF	1		
CAS: 919-30-2	Pow Log	0.1		
EC: 213-048-4	Potential	Low		
Octamethylcyclotetrasiloxane	BCF	12400		
CAS: 556-67-2	Pow Log	4.45		
EC: 209-136-7	Potential	Very High		

## 12.4 Mobility in soil:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

### **BK-Silicon Neutral Profi**

# SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
Octamethylcyclotetrasiloxane	Koc	Non-applicable	Henry	Non-applicable
CAS: 556-67-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 209-136-7	Surface tension	1,819E-2 N/m (25 °C)	Moist soil	Non-applicable

#### 12.5 Results of PBT and vPvB assessment:

Product contains PBT/vPvB substances: Octamethylcyclotetrasiloxane

#### 12.6 Other adverse effects:

Not described

## SECTION 13: DISPOSAL CONSIDERATIONS

## 13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Dangerous

## Type of waste (Regulation (EU) No 1357/2014):

**HP14 Ecotoxic** 

#### Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See paragraph 6.2.

## Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

# SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

# **SECTION 15: REGULATORY INFORMATION**

# 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains octhilinone (ISO).

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Octamethylcyclotetrasiloxane

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: octhilinone (ISO) (Product-type 6, 7, 8, 9, 10, 11, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

## Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc ....):



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

### **BK-Silicon Neutral Profi**

## SECTION 15: REGULATORY INFORMATION (continued)

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and iokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

## Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

#### Other legislation:

The product could be affected by sectorial legislation

## 15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

## **SECTION 16: OTHER INFORMATION**

### Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

## Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

CLP Regulation (EC) No 1272/2008 (SECTION 2, SECTION 16):

· Precautionary statements

## Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

## Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

## CLP Regulation (EC) No 1272/2008:

Acute Tox. 2: H330 - Fatal if inhaled.

Acute Tox. 3: H301+H311 - Toxic if swallowed or in contact with skin.

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 3: H226 - Flammable liquid and vapour.

Repr. 2: H361f - Suspected of damaging fertility.

Skin Corr. 1: H314 - Causes severe skin burns and eye damage.

Skin Corr. 1B: H314 - Causes severe skin burns and eye damage.

Skin Sens. 1A: H317 - May cause an allergic skin reaction.

## Classification procedure:

Aquatic Chronic 3: Calculation method

# Advice related to training:

Minimal training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

# Principal bibliographical sources:

http://echa.europa.eu

http://eur-lex.europa.eu

# Abbreviations and acronyms:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

## **BK-Silicon Neutral Profi**

# SECTION 16: OTHER INFORMATION (continued)

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor

LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET 
Date of compilation: 04/11/2017 Revised: 04/11/2021 Version: 3 (Replaced 2) Page 11/11