$Safety \ data \ sheet$ This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation



RZ-BLP-104 - BK-EmajlClassic

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1 Product identifier: RZ-BLP-104 - BK-EmajlClassic Other means of identification: Non-applicable 1.2 Relevant identified uses of the substance or mixture and uses advised against: Relevant uses: Protective varnish for wood. For professional users only. Uses advised against: All uses not specified in this section or in section 7.3 1.3 Details of the supplier of the safety data sheet: Banja Komerc Bekament DOO Kralja Petra Prvog 132, 34304 Banja, Aranđelovac, Srbija tel. +381 (0) 34 6777 500 e-mail: laboratorija@bekament.com http://bekament.com 1.4 Emergency telephone number: 911 SECTION 2: HAZARDS IDENTIFICATION Classification of the substance or mixture: 2.1 CLP Regulation (EC) No 1272/2008: Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008. Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Asp. Tox. 1: Aspiration hazard, Category 1, H304 Flam. Lig. 3: Flammable liquids, Category 3, H226 STOT RE 1: Specific target organ toxicity — Repeated exposure, Hazard Category 1 (Inhalation), H372 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336 2.2 Label elements: CLP Regulation (EC) No 1272/2008: Danger Hazard statements: Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Flam. Lig. 3: H226 - Flammable liquid and vapour. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation). STOT SE 3: H336 - May cause drowsiness or dizziness. **Precautionary statements:** P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P273: Avoid release to the environment. P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing. P312: Call a POISON CENTER/doctor if you feel unwell. P331: Do NOT induce vomiting. P501: Dispose of the contents/containers in accordance with the current legislation on waste treatment. Supplementary information: EUH066: Repeated exposure may cause skin dryness or cracking. Substances that contribute to the classification Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) **Additional labeling:** Contains: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclic, aromatic (2-25%) **Other hazards:** 2.3

- CONTINUED ON NEXT PAGE -



SECTION 2: HAZARDS IDENTIFICATION (continued)

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture based on hydrocarbons and additives

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification				
CAS: 64742-82-1	Hydrocarbons, C9-C1	2, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) ⁽¹⁾	Self-classified		
EC: 919-446-0 Index: Non-applicable REACH: 01-2119458049-33- XXXX		Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 3: H226; STOT RE 1: H372; STOT SE 3: H336; EUH066 - Danger		25 - <40 %	

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:



SECTION 5: FIREFIGHTING MEASURES (continued)

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks



SECTION 7: HANDLING AND STORAGE (continued)

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

		Short e	kposure	Long exposure	
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	21 mg/kg	Non-applicable
EC: 919-446-0	Inhalation	570 mg/m ³	Non-applicable	330 mg/m ³	Non-applicable

DNEL (General population):

		Short exposure		Long ex	kposure
Identification		Systemic	Local	Systemic	Local
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)	Oral	Non-applicable	Non-applicable	21 mg/kg	Non-applicable
CAS: 64742-82-1	Dermal	Non-applicable	Non-applicable	12 mg/kg	Non-applicable
EC: 919-446-0	Inhalation	570 mg/m ³	Non-applicable	71 mg/m ³	Non-applicable

PNEC:

Non-applicable

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

	Pictogram	PPE	Labelling	CEN Standard	Remarks
resp	Mandatory piratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.
C Specif	fic protection	for the hands			

- CONTINUED ON NEXT PAGE -



	Pictogram		PPE	Labelling	CEN	Standard		Remarks
	Mandatory hand protection		posable chemical tective gloves	CAT III	EN 16523-	-1:2016+A1:2018 1:2015+A1:2018 2004+A1:2010	manu the	The Breakthrough Time indicated by the facturer must exceed the period during w product is being used. Do not use protect s after the product has come into contact skin.
						e glove materia	l can n	ot be calculated in advance with t
	ability and has and face prote		to be checked p	rior to the app	lication.			
D Lyc	Pictogram		PPE	Labelling	CEN	Standard		Remarks
		F	Face shield	CE	EN EN EN	166:2002 167:2002 168:2002		daily and disinfect periodically according t facturer's instructions. Use if there is a ri splashing.
	Mandatory face			CATI	EN ISC	0 4007:2018		
E Boo	protection ly protection							
	Pictogram		PPE	Labelling	CEN	Standard		Remarks
			able clothing for n against chemical			.149-1,2,3 :2005+A1:2009		or professional use only. Clean periodically cording to the manufacturer's instruction:
	indatory complete body protection	risks, w	ith antistatic and roof properties	CAT III	EN ISO 1398 EN ISO EN ISO EN ISO	2-1:2004/A1:2010 0 6529:2013 0 6530:2005 13688:2013 464:1994		
		against of antistatic	twear for protection chemical risk, with and heat resistant properties	(EN ISO	13287:2013 20345:2011 832-1:2019	R	eplace boots at any sign of deterioration.
	Mandatory foot protection		properties	CAT III				
F Add	litional emerge	ncy meas	sures					
	Emergency mea	asure	St	andards		Emergency measu	ire	Standards
	Emergency sho	ower		5I Z358-1 11, ISO 3864-4:20	011	Eyewash station	5	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Enviro			ntrolo			_,	-	
In acco of both Volati l	the product an e organic con	e commu nd its con npounds	nity legislation fo tainer. For additi ::	onal informatio	on see subse	ection 7.1.D	ecomm	nended to avoid environmental sp
With re	gard to Directi	ve 2010/7	75/EU, this produ	ct has the follo	owing chara	teristics:		
	.C. (Supply):			weight				
V.C	O.C. density at 2	20 ºC:	Non-a	pplicable				
Ave	erage carbon n	umber:	9					
Ave	erage molecula	r weight:	120 g	/mol				
With re	gard to Directi	ve 2004/4	12/EC, this produ	ct which is rea	dy to use ha	as the following	chara	cteristics:
V.C	.C. density at 2	20 °C:	499 k	g/m³ (499 g/l	_)			
EU	limit for the pr	oduct (Ca	it. A.I): 500 g/L	(2010)				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.


*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -



-	
Appearance:	
Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	Not available
Odour:	Solvent
Odour threshold:	Non-applicable *
Volatility:	
Boiling point at atmospheric pressure:	160 °C
Vapour pressure at 20 °C:	Non-applicable *
Vapour pressure at 50 °C:	1560,55 Pa (1,56 kPa)
Evaporation rate at 20 °C:	Non-applicable *
Product description:	
Density at 20 °C:	Non-applicable *
Relative density at 20 °C:	1,1
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	<20,5 mm²/s
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 ºC:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 ºC:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Flammability:	·····
Flash Point:	40 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	Non-applicable *
Lower flammability limit:	Not available
Upper flammability limit:	Not available
Particle characteristics:	New every line la
Median equivalent diameter:	Non-applicable
Other information:	
Information with regard to physical hazard class	
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
Corrosive to metals:	Non-applicable *
Heat of combustion:	Non-applicable *
Aerosols-total percentage (by mass) of flammable components: Other safety characteristics:	Non-applicable *
Surface tension at 20 °C:	Non-applicable *
	Non-applicable *
Refraction index:	Non-applicable *

Safety data sheet



RZ-BLP-104 - BK-EmajlClassic

ECTI	ON 10: STABILITY AND	REACTIVITY							
).1	Reactivity:								
	No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.								
).2	Chemical stability:								
	Chemically stable under the	indicated conditions of sto	orage, handling and use.						
0.3	Possibility of hazardous	reactions:							
	Under the specified conditio	ns, hazardous reactions th	hat lead to excessive tempe	eratures or pressure are n	ot expected.				
	Conditions to avoid:	,	·	·	•				
	Applicable for handling and	storage at room temperat	ture:						
	Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity				
	Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable				
0.5	Incompatible materials:								
	Acids	Water	Oxidising materials	Combustible materials	Others				
	Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases. Can react violently				
	complex mixtures of chemic		ased: carbon dioxide (CO2)), carbon monoxide and ot	her organic compounds.				
ECTI	ON 11: TOXICOLOGICA	L INFORMATION							
1.1	Information on toxicolog	ical effects:							
	The experimental information	n related to the toxicologi	ical properties of the produ	ıct itself is not available					
	Dangerous health implic	ations:							
	In case of exposure that is a adverse effects on health m A- Ingestion (acute effect):	ay result, depending on th	5	n the recommended occup	pational exposure limits,				
	- Acute toxicity · Base	d on available data, the cl	lassification suitenia and not	mot as it doos not contai	in substances classified as				

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for inhalation. For more information see section 3.

- Corrosivity/Irritability: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for skin contact. For more information see section 3.

- Contact with the eyes: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatics (2-25%) (3)

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

E- Sensitizing effects:



SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Serious health effects in the case of prolonged inhalation, including death, serious functional disorders or morphological changes of toxicological importance.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

The consumption of a considerable dose can cause pulmonary damage.

Other information:

Non-applicable

Specific toxicology information on the substances:

Not available

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
Hydrocarbons, C9-C12, n-alkanes, isoalkanes, cyclics, aromatic 25%)	cs (2- LC50	>1 - 10 (96 h)		Fish
CAS: 64742-82-1	EC50	>1 - 10 (48 h)		Crustacean
EC: 919-446-0	EC50	>1 - 10 (72 h)		Algae
12.2 Persistence and degradability:		•		•
Not available				
2.3 Bioaccumulative potential:				
Not available				
12.4 Mahility in saily				

12.4 Mobility in soil:

Not available

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation

BEKAMENT

RZ-BLP-104 - BK-EmajlClassic

SECTION 12: ECOLOGICAL INFORMATION (continued)

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land: With regard to ADR 2021 and RID 2021: 14.1 UN number: UN1306 14.2 UN proper shipping name: WOOD PRESERVATIVES, LIQUID 14.3 Transport hazard class(es): 3 Labels: 3 14.4 Packing group: III 14.5 Environmental hazards: Yes 14.6 Special precautions for user Non-applicable Special regulations: Tunnel restriction code: D/E Physico-Chemical properties: see section 9 Limited quantities: 5 L 14.7 Transport in bulk according Non-applicable to Annex II of Marpol and the **IBC Code:** Transport of dangerous goods by sea: With regard to IMDG 39-18:

Safety data sheet

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation



RZ-BLP-104 - BK-EmajlClassic

SECTION 14: TRANSPOR	RT IN	NFORMATION (continued)	
1	14 1	UN number:	UN1306
		UN proper shipping name:	WOOD PRESERVATIVES, LIQUID
		Transport hazard class(es):	3
		Labels:	3
V V 1	14.4	Packing group:	III
1	14.5	Marine pollutant:	Yes
1	14.6	Special precautions for user	
		Special regulations:	955, 223
		EmS Codes:	F-E, S-D
		Physico-Chemical properties:	see section 9
		Limited quantities:	5 L
		Segregation group:	Non-applicable
1	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable
Transport of dang	gerou	s goods by air:	
With regard to IATA	/ICAC	0 2022:	
<u> </u>	14.1	UN number:	UN1306
<"₽>< ¥₂>1	14.2	UN proper shipping name:	WOOD PRESERVATIVES, LIQUID
	14.3	Transport hazard class(es):	3
		Labels:	3
1	14.4	Packing group:	III
1	14.5	Environmental hazards:	Yes
1	14.6	Special precautions for user	
		Physico-Chemical properties:	see section 9
1	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: Non-applicable

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000
E2	ENVIRONMENTAL HAZARDS	200	500

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

--ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

This SDS is an English translation of Regulation (EU) nº 2015/830, without any country-specific legislation



RZ-BLP-104 - BK-EmajlClassic

SECTION 15: REGULATORY INFORMATION (continued)

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.: Non-applicable

Texts of the legislative phrases mentioned in section 2:

- H336: May cause drowsiness or dizziness.
- H411: Toxic to aquatic life with long lasting effects.
- H372: Causes damage to organs through prolonged or repeated exposure (Inhalation).
- H304: May be fatal if swallowed and enters airways.
- H226: Flammable liquid and vapour.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways. Flam. Liq. 3: H226 - Flammable liquid and vapour. STOT RE 1: H372 - Causes damage to organs through prolonged or repeated exposure (Inhalation). STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

STOT SE 3: Calculation method Aquatic Chronic 2: Calculation method STOT RE 1: Calculation method Asp. Tox. 1: Calculation method Flam. Liq. 3: Calculation method (2.6.4.3)

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation COD: Chemical Oxygen Demand BOD5: 5day biochemical oxygen demand BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50 LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon UFI: unique formula identifier IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.