

This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: RZ-BLP-102-01 - BK-Nitro

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Dilutants. For professional users only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

Banja Komerc Bekament DOO Kralja Petra Prvog 132, 34304 Banja, Aranđelovac, Srbija tel. +381 (0) 34 6777 500 e-mail: laboratorija@bekament.com http://bekament.com

1.4 Emergency telephone number: 911

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Acute Tox. 4: Acute toxicity if swallowed, Category 4, H302

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

Carc. 2: Carcinogenicity, Category 2, H351 Eye Irrit. 2: Eye irritation, Category 2, H319 Flam. Liq. 2: Flammable liquids, Category 2, H225

Repr. 2: Reproductive toxicity, Category 2, H361d

Repr. 2: Reproductive toxicity, Category 2, H361d

STOT SE 2: Specific target organ toxicity — single exposure, Hazard Category 2, H371

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Danger







Hazard statements:

Acute Tox. 4: H302 - Harmful if swallowed.

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Carc. 2: H351 - Suspected of causing cancer.

Eve Irrit. 2: H319 - Causes serious eve irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Repr. 2: H361d - Suspected of damaging the unborn child.

STOT SE 2: H371 - May cause damage to organs.

Precautionary statements:

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260: Do not breathe dust/fume/gas/mist/vapours/spray.

P273: Avoid release to the environment.

P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.

P308+P311: IF exposed or concerned: Call a POISON CENTER/doctor.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

Additional labeling:



RZ-BLP-102-01 - BK-Nitro

SECTION 2: HAZARDS IDENTIFICATION (continued)

Contains: Ethyl acetate, acetone, dichloromethane, toluene, methanol and tetrahydrofuran.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Mixture based on aromatising substances and preparations.

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 141-78-6 EC: 205-500-4	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	10 - <40 %
Index: 607-022-00-5 REACH: 01-2119475103-46- XXXX	Lye Int. 2. 11519, Haill. Ed. 2. 11223, 3101 3E 3. 11530, E011000 - Danger	10 - <40 %
CAS: 67-64-1	acetone(1) ATP CLP00	
EC: 200-662-2 Index: 606-001-00-8 REACH: 01-2119471330-49- XXXX	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	10 - <35 %
CAS: 75-09-2	Dichloromethane ⁽²⁾ ATP CLP00	
EC: 200-838-9 Index: 602-004-00-3 REACH: 01-2119480404-41- XXXX	Regulation 1272/2008 Carc. 2: H351 - Warning	5 - <10 %
CAS: 79-20-9	methyl acetate(1) ATP CLP00	
EC: 201-185-2 Index: 607-021-00-X REACH: 01-2119459211-47- XXXX	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	1 - <10 %
CAS: 108-88-3	Toluene ⁽¹⁾ ATP CLP00	
EC: 203-625-9 Index: 601-021-00-3 REACH: 01-2119471310-51- XXXX	Regulation 1272/2008 Asp. Tox. 1: H304; Flam. Liq. 2: H225; Repr. 2: H361d; Skin Irrit. 2: H315; STOT RE 2: H373; STOT SE 3: H336 - Danger	1 - <10 %
CAS: 67-56-1	methanol(1) ATP CLP00	
EC: 200-659-6 Index: 603-001-00-X REACH: 01-2119433307-44- XXXX	Regulation 1272/2008 Acute Tox. 3: H301+H311+H331; Flam. Liq. 2: H225; STOT SE 1: H370 - Danger	1 - <9 %
CAS: 64-17-5	ethanol ⁽¹⁾ ATP CLP00	
EC: 200-578-6 Index: 603-002-00-5 REACH: 01-2119457610-43- XXXX	Regulation 1272/2008 Flam. Liq. 2: H225 - Danger	1 - <5 %
CAS: 67-63-0	propan-2-ol ⁽¹⁾ ATP CLP00	
EC: 200-661-7 Index: 603-117-00-0 REACH: 01-2119457558-25- XXXX	Regulation 1272/2008 Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336 - Danger	1 - <5 %
CAS: 109-99-9	tetrahydrofuran ⁽¹⁾ ATP ATP03	
EC: 203-726-8 Index: 603-025-00-0 REACH: 01-2119444314-46- XXXX	Regulation 1272/2008	1 - <4 %
CAS: 107-46-0	Hexamethyldisiloxane ⁽¹⁾ Self-classified	
EC: 203-492-7 Index: Non-applicable REACH: 01-2119496108-31- XXXX	Regulation 1272/2008 Aquatic Acute 1: H400; Aquatic Chronic 2: H411; Flam. Liq. 2: H225 - Danger	0.5 - <4 %

⁽¹⁾ Voluntarily-listed substance failing to meet any of the criteria set out in Regulation (EU) No. 2015/830

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

⁽²⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2015/830



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Request medical assistance immediately, showing the SDS of this product. Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. In the case of loss of consciousness do not administer anything orally unless supervised by a doctor. Rinse out the mouth and throat, as they may have been affected during ingestion. Keep the person affected at rest.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2).

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

For emergency responders:

See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems defined in Directive 2014/34/EC (ATEX 100) and with the minimum requirements for protecting the security and health of workers under the selection criteria of Directive 1999/92/EC (ATEX 137). Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

PREGNANT WOMEN SHOULD NOT BE EXPOSED TO THIS PRODUCT. Transfer in designated areas that comply with the necessary safety conditions (emergency showers and eyewash stations in close proximity), using personal protection equipment, especially on the hands and face (See section 8). Limit manual transfers to small amounts only. Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION



RZ-BLP-102-01 - BK-Nitro

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Oc	cupational exposur	e limits
Ethyl acetate	IOELV (8h)	200 ppm	734 mg/m ³
CAS: 141-78-6 EC: 205-500-4	IOELV (STEL)	400 ppm	1468 mg/m ³
acetone	IOELV (8h)	500 ppm	1210 mg/m ³
CAS: 67-64-1 EC: 200-662-2	IOELV (STEL)		
Dichloromethane	IOELV (8h)	100 ppm	353 mg/m ³
CAS: 75-09-2	IOELV (STEL)	200 ppm	706 mg/m ³
Toluene	IOELV (8h)	50 ppm	192 mg/m ³
CAS: 108-88-3	IOELV (STEL)	100 ppm	384 mg/m ³
methanol	IOELV (8h)	200 ppm	260 mg/m ³
CAS: 67-56-1 EC: 200-659-6	IOELV (STEL)		
tetrahydrofuran	IOELV (8h)	50 ppm	150 mg/m ³
CAS: 109-99-9	IOELV (STEL)	100 ppm	300 mg/m ³

DNEL (Workers):

		Short	Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local	
Ethyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	63 mg/kg	Non-applicable	
EC: 205-500-4	Inhalation	1468 mg/m³	1468 mg/m ³	734 mg/m³	734 mg/m ³	
acetone	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	186 mg/kg	Non-applicable	
EC: 200-662-2	Inhalation	Non-applicable	2420 mg/m ³	1210 mg/m³	Non-applicable	
Dichloromethane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 75-09-2	Dermal	Non-applicable	Non-applicable	12 mg/kg	Non-applicable	
EC: 200-838-9	Inhalation	Non-applicable	Non-applicable	176 mg/m³	Non-applicable	
methyl acetate	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 79-20-9	Dermal	Non-applicable	Non-applicable	43 mg/kg	Non-applicable	
EC: 201-185-2	Inhalation	3777 mg/m ³	Non-applicable	300 mg/m ³	620 mg/m ³	
Toluene	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	384 mg/kg	Non-applicable	
EC: 203-625-9	Inhalation	384 mg/m ³	384 mg/m³	192 mg/m³	192 mg/m ³	
methanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 67-56-1	Dermal	20 mg/kg	Non-applicable	20 mg/kg	Non-applicable	
EC: 200-659-6	Inhalation	130 mg/m ³	130 mg/m ³	130 mg/m ³	130 mg/m ³	
ethanol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 64-17-5	Dermal	Non-applicable	Non-applicable	343 mg/kg	Non-applicable	
EC: 200-578-6	Inhalation	Non-applicable	Non-applicable	950 mg/m ³	Non-applicable	
propan-2-ol	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	888 mg/kg	Non-applicable	
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	500 mg/m ³	Non-applicable	
tetrahydrofuran	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 109-99-9	Dermal	Non-applicable	Non-applicable	12,6 mg/kg	Non-applicable	
EC: 203-726-8	Inhalation	96 mg/m ³	300 mg/m ³	72,4 mg/m³	150 mg/m ³	
Hexamethyldisiloxane	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable	
CAS: 107-46-0	Dermal	Non-applicable	Non-applicable	333 mg/kg	Non-applicable	
EC: 203-492-7	Inhalation	Non-applicable	Non-applicable	53,4 mg/m ³	Non-applicable	



RZ-BLP-102-01 - BK-Nitro

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (co	ontinued)
--	-----------

		Short	exposure	Long	Long exposure	
Identification		Systemic	Local	Systemic	Local	
Ethyl acetate	Oral	Non-applicable	Non-applicable	4,5 mg/kg	Non-applicable	
CAS: 141-78-6	Dermal	Non-applicable	Non-applicable	37 mg/kg	Non-applicable	
EC: 205-500-4	Inhalation	734 mg/m³	734 mg/m ³	367 mg/m ³	367 mg/m ³	
acetone	Oral	Non-applicable	Non-applicable	62 mg/kg	Non-applicable	
CAS: 67-64-1	Dermal	Non-applicable	Non-applicable	62 mg/kg	Non-applicable	
EC: 200-662-2	Inhalation	Non-applicable	Non-applicable	200 mg/m ³	Non-applicable	
Dichloromethane	Oral	Non-applicable	Non-applicable	0,06 mg/kg	Non-applicable	
CAS: 75-09-2	Dermal	Non-applicable	Non-applicable	5,82 mg/kg	Non-applicable	
EC: 200-838-9	Inhalation	Non-applicable	Non-applicable	44 mg/m³	Non-applicable	
methyl acetate	Oral	203 mg/kg	Non-applicable	21,5 mg/kg	Non-applicable	
CAS: 79-20-9	Dermal	203 mg/kg	Non-applicable	21,5 mg/kg	Non-applicable	
EC: 201-185-2	Inhalation	3777 mg/m ³	Non-applicable	64 mg/m ³	133 mg/m ³	
Toluene	Oral	Non-applicable	Non-applicable	8,13 mg/kg	Non-applicable	
CAS: 108-88-3	Dermal	Non-applicable	Non-applicable	226 mg/kg	Non-applicable	
EC: 203-625-9	Inhalation	226 mg/m ³	226 mg/m ³	56,5 mg/m ³	56,5 mg/m ³	
methanol	Oral	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable	
CAS: 67-56-1	Dermal	4 mg/kg	Non-applicable	4 mg/kg	Non-applicable	
EC: 200-659-6	Inhalation	26 mg/m ³	26 mg/m ³	26 mg/m ³	26 mg/m ³	
ethanol	Oral	Non-applicable	Non-applicable	87 mg/kg	Non-applicable	
CAS: 64-17-5	Dermal	Non-applicable	Non-applicable	206 mg/kg	Non-applicable	
EC: 200-578-6	Inhalation	Non-applicable	Non-applicable	114 mg/m³	Non-applicable	
propan-2-ol	Oral	Non-applicable	Non-applicable	26 mg/kg	Non-applicable	
CAS: 67-63-0	Dermal	Non-applicable	Non-applicable	319 mg/kg	Non-applicable	
EC: 200-661-7	Inhalation	Non-applicable	Non-applicable	89 mg/m ³	Non-applicable	
tetrahydrofuran	Oral	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable	
CAS: 109-99-9	Dermal	Non-applicable	Non-applicable	1,5 mg/kg	Non-applicable	
EC: 203-726-8	Inhalation	52 mg/m ³	150 mg/m ³	13 mg/m³	75 mg/m³	
Hexamethyldisiloxane	Oral	Non-applicable	Non-applicable	0,27 mg/kg	Non-applicable	
CAS: 107-46-0	Dermal	Non-applicable	Non-applicable	167 mg/kg	Non-applicable	
EC: 203-492-7	Inhalation	Non-applicable	Non-applicable	13,3 mg/m ³	Non-applicable	

PNEC:

Identification				
Ethyl acetate	STP	650 mg/L	Fresh water	0,24 mg/L
CAS: 141-78-6	Soil	0,148 mg/kg	Marine water	0,024 mg/L
EC: 205-500-4	Intermittent	1,65 mg/L	Sediment (Fresh water)	1,15 mg/kg
	Oral	0,2 g/kg	Sediment (Marine water)	0,115 mg/kg
acetone	STP	100 mg/L	Fresh water	10,6 mg/L
CAS: 67-64-1	Soil	29,5 mg/kg	Marine water	1,06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh water)	30,4 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	3,04 mg/kg
Dichloromethane	STP	26 mg/L	Fresh water	0,31 mg/L
CAS: 75-09-2	Soil	0,33 mg/kg	Marine water	0,031 mg/L
EC: 200-838-9	Intermittent	0,27 mg/L	Sediment (Fresh water)	2,57 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,26 mg/kg
Toluene	STP	13,61 mg/L	Fresh water	0,68 mg/L
CAS: 108-88-3	Soil	2,89 mg/kg	Marine water	0,68 mg/L
EC: 203-625-9	Intermittent	0,68 mg/L	Sediment (Fresh water)	16,39 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	16,39 mg/kg
methanol	STP	100 mg/L	Fresh water	20,8 mg/L
CAS: 67-56-1	Soil	100 mg/kg	Marine water	2,08 mg/L
EC: 200-659-6	Intermittent	1540 mg/L	Sediment (Fresh water)	77 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,7 mg/kg

Date of compilation: 11/09/2017 Version: 1 Page 6/18



RZ-BLP-102-01 - BK-Nitro

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
ethanol	STP	580 mg/L	Fresh water	0,96 mg/L
CAS: 64-17-5	Soil	0,63 mg/kg	Marine water	0,79 mg/L
EC: 200-578-6	Intermittent	2,75 mg/L	Sediment (Fresh water)	3,6 mg/kg
	Oral	0,38 g/kg	Sediment (Marine water)	2,9 mg/kg
propan-2-ol	STP	2251 mg/L	Fresh water	140,9 mg/L
CAS: 67-63-0	Soil	28 mg/kg	Marine water	140,9 mg/L
EC: 200-661-7	Intermittent	140,9 mg/L	Sediment (Fresh water)	552 mg/kg
	Oral	0,16 g/kg	Sediment (Marine water)	552 mg/kg
tetrahydrofuran	STP	4,6 mg/L	Fresh water	4,32 mg/L
CAS: 109-99-9	Soil	2,13 mg/kg	Marine water	0,432 mg/L
EC: 203-726-8	Intermittent	21,6 mg/L	Sediment (Fresh water)	23,3 mg/kg
	Oral	0,067 g/kg	Sediment (Marine water)	2,33 mg/kg
Hexamethyldisiloxane	STP	10 mg/L	Fresh water	0,002 mg/L
CAS: 107-46-0	Soil	0,083 mg/kg	Marine water	0 mg/L
EC: 203-492-7	Intermittent	0,003 mg/L	Sediment (Fresh water)	8,9 mg/kg
	Oral	0,0053 g/kg	Sediment (Marine water)	0,89 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory respiratory tract protection	Filter mask for gases and vapours	CAT III	EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands


I	Pictogram	PPE	Labelling	CEN Standard	Remarks
	Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CAT III	EN 420:2004+A1:2010	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Face shield	CAT II	EN 166:2002 EN 167:2002 EN 168:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection





RZ-BLP-102-01 - BK-Nitro

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory complete body protection	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	CAT III	EN 1149-1,2,3 EN 13034:2005+A1:2009 EN ISO 13982-1:2004/A1:2010 EN ISO 6529:2013 EN ISO 6530:2005 EN ISO 13688:2013 EN 464:1994	For professional use only. Clean periodically according to the manufacturer's instructions.
Mandatory foot protection	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	CAT III	EN ISO 13287:2013 EN ISO 20345:2011 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 100 % weight
V.O.C. density at 20 °C: Non-applicable

Average carbon number: 3,05

Average molecular weight: 74,16 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Colour:

Not available

Odour:

Odour threshold:

Liquid

Characteristic

Not available

Characteristic

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: >35 °C

Vapour pressure at 20 °C: Non-applicable *

Vapour pressure at 50 °C: 69415,86 Pa (69,42 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: Non-applicable *

Relative density at 20 °C: 0,87

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 40 °C:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Concentration: Non-applicable * Non-applicable * pH: Vapour density at 20 °C: Non-applicable * Partition coefficient n-octanol/water 20 °C: Non-applicable * Solubility in water at 20 °C: Non-applicable * Solubility properties: Non-applicable * Decomposition temperature: Non-applicable * Non-applicable * Melting point/freezing point:

Flammability:

Flash Point: <21 °C

Flammability (solid, gas):

Autoignition temperature:

Lower flammability limit:

Upper flammability limit:

Not available

Not available

Particle characteristics:

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Non-applicable *

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Companyate:

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C: Non-applicable *

Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

Contains substances which require external energy for spontaneous decomposition. Form explosive peroxides when distilled, evaporated or otherwise concentrated.



RZ-BLP-102-01 - BK-Nitro

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- B- Inhalation (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
 - IARC: Dichloromethane (2A); Toluene (3); ethanol (1); propan-2-ol (3); tetrahydrofuran (2B)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Suspected of damaging the unborn child.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Harmful effects for health in the case of ingestion, contact with the skin or inhalation after a single exposure, resulting in depression of the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion and, in serious cases, loss of consciousness.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met. However, it does contain substances which are classified as dangerous due to repetitive exposure. For more information see section 3.
 - Skin: Repeated exposure may cause skin dryness or cracking
- H- Aspiration hazard:

Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
Ethyl acetate	LD50 oral	4100 mg/kg	Rat
CAS: 141-78-6	LD50 dermal	20000 mg/kg	Rabbit
EC: 205-500-4	LC50 inhalation	Non-applicable	
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation	76 mg/L (4 h)	Rat



RZ-BLP-102-01 - BK-Nitro

Identification	A	Acute toxicity	Genu
methyl acetate	LD50 oral	6482 mg/kg	Rat
CAS: 79-20-9	LD50 dermal	18684 mg/kg	Guinean
EC: 201-185-2	LC50 inhalation	75 mg/L (4 h)	Rabbi
Toluene	LD50 oral	5580 mg/kg	Rat
CAS: 108-88-3	LD50 dermal	12124 mg/kg	Rat
EC: 203-625-9	LC50 inhalation	28,1 mg/L (4 h)	Rat
methanol	LD50 oral	>5000 mg/kg	Rat
CAS: 67-56-1	LD50 dermal	300 mg/kg	Rabbi
EC: 200-659-6	LC50 inhalation	3 mg/L (4 h)	Rat
ethanol	LD50 oral	6200 mg/kg	Rat
CAS: 64-17-5	LD50 dermal	20000 mg/kg	Rabbi
EC: 200-578-6	LC50 inhalation	124,7 mg/L (4 h)	Rat
propan-2-ol	LD50 oral	5280 mg/kg	Rat
CAS: 67-63-0	LD50 dermal	12800 mg/kg	Rat
EC: 200-661-7	LC50 inhalation	72,6 mg/L (4 h)	Rat
tetrahydrofuran	LD50 oral	>5000 mg/kg	Rat
CAS: 109-99-9	LD50 dermal	Non-applicable	
EC: 203-726-8	LC50 inhalation	Non-applicable	
Dichloromethane	LD50 oral	Non-applicable	
CAS: 75-09-2	LD50 dermal	Non-applicable	
EC: 200-838-9	LC50 inhalation	86 mg/L (4 h)	Rat

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity:

Product-specific aquatic toxicity:

	Acute toxicity	Species	Genus
LC50	12,23 mg/L (96 h)	Non-applicable	Fish

Substance-specific aquatic toxicity:

Acute toxicity:

Identification	Identification Concentration		Species	Genus	
Ethyl acetate	LC50	230 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 141-78-6	EC50	717 mg/L (48 h)	Daphnia magna	Crustacean	
EC: 205-500-4	EC50	3300 mg/L (48 h)	Scenedesmus subspicatus	Algae	



RZ-BLP-102-01 - BK-Nitro

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean
EC: 200-662-2	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae
Dichloromethane	LC50	330 mg/L (96 h)	Pimephales promelas	Fish
CAS: 75-09-2	EC50	270 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-838-9	EC50	2300 mg/L (3 h)	Chlorella vulgaris	Algae
methyl acetate	LC50	320 mg/L (96 h)	Pimephales promelas	Fish
CAS: 79-20-9	EC50	1026,7 mg/L (48 h)	Daphnia magna	Crustacean
EC: 201-185-2	EC50	120 mg/L (72 h)	Scenedesmus subspicatus	Algae
Toluene	LC50	5,5 mg/L (96 h)	Oncorhynchus kisutch	Fish
CAS: 108-88-3	EC50	3,78 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
EC: 203-625-9	EC50	Non-applicable		
methanol	LC50	15400 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 67-56-1	EC50	12000 mg/L (96 h)	Nitrocra spinipes	Crustacean
EC: 200-659-6	EC50	530 mg/L (168 h)	Microcystis aeruginosa	Algae
ethanol	LC50	11000 mg/L (96 h)	Alburnus alburnus	Fish
CAS: 64-17-5	EC50	9268 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-578-6	EC50	1450 mg/L (192 h)	Microcystis aeruginosa	Algae
propan-2-ol	LC50	9640 mg/L (96 h)	Pimephales promelas	Fish
CAS: 67-63-0	EC50	13299 mg/L (48 h)	Daphnia magna	Crustacean
EC: 200-661-7	EC50	1000 mg/L (72 h)	Scenedesmus subspicatus	Algae
tetrahydrofuran	LC50	2160 mg/L (96 h)	Pimephales promelas	Fish
CAS: 109-99-9	EC50	Non-applicable		
EC: 203-726-8	EC50	Non-applicable		
Hexamethyldisiloxane	LC50	0,46 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 107-46-0	EC50	Non-applicable		
EC: 203-492-7	EC50	Non-applicable		

Chronic toxicity:

Identification	Concentration		Species	Genus
Ethyl acetate	NOEC	9,65 mg/L	Pimephales promelas	Fish
CAS: 141-78-6 EC: 205-500-4	NOEC	2,4 mg/L	Daphnia magna	Crustacean
acetone	NOEC	Non-applicable		
CAS: 67-64-1 EC: 200-662-2	NOEC	2212 mg/L	Daphnia magna	Crustacean
Dichloromethane	NOEC	357 mg/L	Pimephales promelas	Fish
CAS: 75-09-2 EC: 200-838-9	NOEC	Non-applicable		



RZ-BLP-102-01 - BK-Nitro

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification		Concentration	Species	Genus
methanol	NOEC	15800 mg/L	Oryzias latipes	Fish
CAS: 67-56-1 EC: 200-659-6	NOEC	122 mg/L	Daphnia magna	Crustacean
ethanol	NOEC	250 mg/L	Danio rerio	Fish
CAS: 64-17-5 EC: 200-578-6	NOEC	2 mg/L	Ceriodaphnia dubia	Crustacean
tetrahydrofuran	NOEC	216 mg/L	Pimephales promelas	Fish
CAS: 109-99-9 EC: 203-726-8	NOEC	Non-applicable		
Hexamethyldisiloxane	NOEC	0,04 mg/L	Cyprinus carpio	Fish
CAS: 107-46-0 EC: 203-492-7	NOEC	0,08 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	De	gradability	Biode	egradability
Ethyl acetate	BOD5	1,36 g O2/g	Concentration	100 mg/L
CAS: 141-78-6	COD	1,69 g O2/g	Period	14 days
EC: 205-500-4	BOD5/COD	0,8	% Biodegradable	83 %
acetone	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-64-1	COD	Non-applicable	Period	28 days
EC: 200-662-2	BOD5/COD	Non-applicable	% Biodegradable	96 %
Dichloromethane	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 75-09-2	COD	Non-applicable	Period	28 days
EC: 200-838-9	BOD5/COD	Non-applicable	% Biodegradable	13 %
methyl acetate	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 79-20-9	COD	Non-applicable	Period	14 days
EC: 201-185-2	BOD5/COD	Non-applicable	% Biodegradable	92 %
Toluene	BOD5	2,5 g O2/g	Concentration	100 mg/L
CAS: 108-88-3	COD	Non-applicable	Period	14 days
EC: 203-625-9	BOD5/COD	Non-applicable	% Biodegradable	100 %
methanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 67-56-1	COD	1,42 g O2/g	Period	14 days
EC: 200-659-6	BOD5/COD	Non-applicable	% Biodegradable	92 %
ethanol	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 64-17-5	COD	Non-applicable	Period	14 days
EC: 200-578-6	BOD5/COD	Non-applicable	% Biodegradable	89 %
propan-2-ol	BOD5	1,19 g O2/g	Concentration	100 mg/L
CAS: 67-63-0	COD	2,23 g O2/g	Period	14 days
EC: 200-661-7	BOD5/COD	0,53	% Biodegradable	86 %



RZ-BLP-102-01 - BK-Nitro

Identification	[egradability	E	Biodegradability	
tetrahydrofuran	BOD5	Non-applicable	Concentration	100 mg/L	
CAS: 109-99-9	COD	Non-applicable	Period	14 days	
EC: 203-726-8	BOD5/COD	Non-applicable	% Biodegradable	100 %	
Bioaccumulative potential:					
Ide	ntification		Bioa	ccumulation potential	
Ethyl acetate			BCF	30	
CAS: 141-78-6			Pow Log	0.73	
EC: 205-500-4			Potential	Moderate	
acetone			BCF	1	
CAS: 67-64-1			Pow Log	-0.24	
EC: 200-662-2			Potential	Low	
Dichloromethane			BCF	6	
CAS: 75-09-2			Pow Log	1.25	
EC: 200-838-9			Potential	Low	
methyl acetate			BCF	0.8	
CAS: 79-20-9			Pow Log	0.18	
EC: 201-185-2			Potential	Low	
Toluene			BCF	90	
CAS: 108-88-3			Pow Log	2.73	
EC: 203-625-9			Potential	Moderate	
methanol			BCF	3	
CAS: 67-56-1			Pow Log	-0.77	
EC: 200-659-6			Potential	Low	
ethanol			BCF	3	
CAS: 64-17-5			Pow Log	-0.31	
EC: 200-578-6			Potential	Low	
propan-2-ol			BCF	3	
CAS: 67-63-0			Pow Log	0.05	
EC: 200-661-7			Potential	Low	
tetrahydrofuran			BCF	3	
CAS: 109-99-9			Pow Log	0.46	
EC: 203-726-8			Potential	Low	



RZ-BLP-102-01 - BK-Nitro

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorp	otion/desorption	Volatility	
Ethyl acetate	Кос	59	Henry	13,58 Pa·m³/mol
CAS: 141-78-6	Conclusion	Very High	Dry soil	Yes
EC: 205-500-4	Surface tension	2,324E-2 N/m (25 °C)	Moist soil	Yes
acetone	Кос	1	Henry	2,93 Pa·m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
EC: 200-662-2	Surface tension	2,304E-2 N/m (25 °C)	Moist soil	Yes
Dichloromethane	Koc	Non-applicable	Henry	Non-applicable
CAS: 75-09-2	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-838-9	Surface tension	2,877E-2 N/m (25 °C)	Moist soil	Non-applicable
methyl acetate	Koc	Non-applicable	Henry	Non-applicable
CAS: 79-20-9	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 201-185-2	Surface tension	2,454E-2 N/m (25 °C)	Moist soil	Non-applicable
Toluene	Koc	178	Henry	672,8 Pa·m³/mol
CAS: 108-88-3	Conclusion	Moderate	Dry soil	Yes
EC: 203-625-9	Surface tension	2,793E-2 N/m (25 °C)	Moist soil	Yes
methanol	Кос	Non-applicable	Henry	Non-applicable
CAS: 67-56-1	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 200-659-6	Surface tension	2,355E-2 N/m (25 °C)	Moist soil	Non-applicable
ethanol	Кос	1	Henry	4,61E-1 Pa·m³/mol
CAS: 64-17-5	Conclusion	Very High	Dry soil	Yes
EC: 200-578-6	Surface tension	2,339E-2 N/m (25 °C)	Moist soil	Yes
propan-2-ol	Кос	1.5	Henry	8,207E-1 Pa·m³/mol
CAS: 67-63-0	Conclusion	Very High	Dry soil	Yes
EC: 200-661-7	Surface tension	2,24E-2 N/m (25 °C)	Moist soil	Yes
tetrahydrofuran	Кос	23	Henry	7,19 Pa·m³/mol
CAS: 109-99-9	Conclusion	Very High	Dry soil	Yes
EC: 203-726-8	Surface tension	2,498E-2 N/m (25 °C)	Moist soil	Yes
Hexamethyldisiloxane	Кос	Non-applicable	Henry	Non-applicable
CAS: 107-46-0	Conclusion	Non-applicable	Dry soil	Non-applicable
EC: 203-492-7	Surface tension	1,539E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)	
	It is not possible to assign a specific code, as it depends on the intended use by the user	Dangerous	

Type of waste (Regulation (EU) No 1357/2014):

HP3 Flammable, HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP7 Carcinogenic, HP10 Toxic for reproduction, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 13: DISPOSAL CONSIDERATIONS (continued)

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2021 and RID 2021:



14.1 UN number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethyl acetate)

No

 14.3
 Transport hazard class(es):
 3

 Labels:
 3

 14.4
 Packing group:
 II

14.6 Special precautions for user

14.5 Environmental hazards:

Special regulations: 274, 601, 640D

Tunnel restriction code: D/E

Physico-Chemical properties: see section 9

Limited quantities: 1 L

14.7 Transport in bulk according Non-applicable to Annex II of Marpol and the

IBC Code:

Transport of dangerous goods by sea:

With regard to IMDG 39-18:

14.1 UN number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethyl acetate)

 14.3
 Transport hazard class(es):
 3

 Labels:
 3

 14.4
 Packing group:
 II

 14.5
 Marine pollutant:
 No

 14.6
 Special precautions for user

Special regulations: 274
EmS Codes: F-E, S-E
Physico-Chemical properties: see section 9

Limited quantities: 1 L

Segregation group: Non-applicable

14.7 Transport in bulk according to Annex II of Marpol and the

IBC Code:

Transport of dangerous goods by air:

With regard to IATA/ICAO 2022:



14.1 UN number: UN1993

14.2 UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (Ethyl acetate)

14.3 Transport hazard class(es): 3
Labels: 3
14.4 Packing group: II
14.5 Environmental hazards: No

14.6 Special precautions for user

Physico-Chemical properties: see section 9 **14.7 Transport in bulk according** Non-applicable

to Annex II of Marpol and the

IBC Code:

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:



This SDS is an English translation of Regulation (EU) n^{o} 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains ethanol.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: ethanol (Product-type 1, 2, 4, 6); propan-2-ol (Product-type 1, 2, 4)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Section	Description	Lower-tier requirements	Upper-tier requirements
P5c	FLAMMABLE LIQUIDS	5000	50000

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Contains more than 0.1 % of Toluene by weight. Shall not be placed on the market, or used, as a substance or in mixtures in a concentration equal to or greater than 0,1 % by weight where the substance or mixture is used in adhesives or spray paints intended for supply to the general public.

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays.
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (Regulation (EC) No 2015/830).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Non-applicable

Texts of the legislative phrases mentioned in section 2:

H225: Highly flammable liquid and vapour.

H302: Harmful if swallowed.

H319: Causes serious eye irritation.

H351: Suspected of causing cancer.

H412: Harmful to aquatic life with long lasting effects.

H361d: Suspected of damaging the unborn child.

H371: May cause damage to organs.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:



This SDS is an English translation of Regulation (EU) no 2015/830, without any country-specific legislation

RZ-BLP-102-01 - BK-Nitro

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 3: H301+H311+H331 - Toxic if swallowed, in contact with skin or if inhaled.

Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.

Carc. 2: H351 - Suspected of causing cancer. Eye Irrit. 2: H319 - Causes serious eye irritation.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour. Repr. 2: H361d - Suspected of damaging the unborn child.

Skin Irrit. 2: H315 - Causes skin irritation.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 1: H370 - Causes damage to organs. STOT SE 3: H335 - May cause respiratory irritation.

STOT SE 3: H336 - May cause drowsiness or dizziness.

Classification procedure:

Flam. Liq. 2: Calculation method (2.6.4.3)

Acute Tox. 4: Calculation method Eye Irrit. 2: Calculation method Carc. 2: Calculation method Aquatic Chronic 3: Calculation method

Repr. 2: Calculation method

Repr. 2: Calculation method STOT SE 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50 LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET
Date of compilation: 11/09/2017 Version: 1 Page 18/18