

1. IDENTIFICATION OF PRODUCT AND COMPANY

Product trade name: BK-Wood Effect Extra
Product for easy separation of mould and mortar

Data on Manufacturer:

Banja Komerc Bekament DOO
Kralja Petra Prvog 132
Arandjelovac
tel. 034-6777-500
fax. 034-6777-505
e-mail: komercijala@bekament.com

Contact for TSP production:

e-mail: laboratorija@bekament.com

2. DESCRIPTION AND FIELD OF APPLICATION

BK-Wood Effect Extra is a product used for forming of shapes with the rubber mould without sticking of BK-Wood Effect decorative mineral mortar for the mould during the process of work.

3. COMPOSITION

Chemical composition: water based emulsion

4. OTHER CHARACTERISTICS

Appearance: colourless transparent liquid

Density, kg/dm³: ~1,03

Consumption: App. 0.1 l/m² of the finished mortar structure

Packaging: 5 l

5. PREPARATION AND APPLICATION

BK-Wood Effect Extra is applied undiluted to the rubber mould in order to provide easy detaching from BK-Wood Effect decorative mortar during the process of modelling the wooden board structure. BK-Wood Effect Extra is applied to the rubber mould undiluted, with the brush. After each impression, new layer is evenly applied. If needed, remove residuals of decorative mortar from the mould. Lack or insufficient quantity of product might result in sticking of the mould for mortar, pulling out of the mass and poor final results.

Application temperature: the temperature of air and base during the installation

should be from +5 °C to +30 °C. Avoid direct sunlight, fog, wind and rain.

6. TOOL CLEANING

Tools should be thoroughly cleaned and washed with water immediately after use. If the tool is not washed immediately after use, hardened residuals should be mechanically removed.

7. HANDLING AND STORING

Proper use does not require any particular safety measures. Keep out of reach of children.

Product expiry and storing: 18 months in originally closed packaging. Store at the temperature from +5°C to +25°C, in a dry and aired room. Avoid direct sunlight and heat. Production date printed at the packaging.

8. INFORMATION ON REGULATIONS

Additional marking:

EUH208 Contains 1,2- Benzisothiazol-3(2H)-one and mixture of 5-chloro-2-methyl-2H-isothiazolinone -3-on and

2-methyl-2H- isothiazolinone -3-on (3:1). Product can cause allergy reactions.

EUH210 Safety sheet available on demand.

9. ECOTOXICOLOGY INFORMATION

Based on earlier experience and the existing information, in proper use, there are no reported negative effects on human health. Avoid uncontrolled discharge into canalization and water flows.

10. METHOD OF DISPOSAL

In accordance with local /regional /European /national regulations.

11. NOTE

Banja Komerc Bekament DOO executes product control in their own laboratories, along with the regular testing in certified laboratories. Technical sheet is the product of our knowledge and experience. All users should use it as our recommendation for achieving best possible results. If the weather and other conditions differ from those explained in our manual, it is recommended to take directions from this manual as general, without guarantee for installation.

Banja Komerc Bekament DOO shall not be held responsible for any damage arising from irregular use or incorrect choosing of the product, as well as for the poor quality

TECHNICAL SHEET OF PRODUCT	Issue:1	Version:0
BK-Wood Effect Extra	RZ-TLP-077-02	Date: 20/09/2022
Prepared by: Mirjana Savić	Approved by: Vesna Jovanović	

of works. It is assumed that the contractor has mastered the techniques of installation and use of various products.

The written text shall in no way be binding for us.

This document replaces all previous versions which shall, starting from the said date, be held invalid.

Date of preparation: 20/09/2022

Previous Version: /

Modified Chapters: /